

ECONOMICAL HIGH HIDING PAINT

777 PVA™



CODE:

DCH

Description:

A cost effective emulsion paint with excellent coverage.

Product Benefits:

For interior walls, ceilings, partitions, etc.
May be used on exterior surfaces in areas of low rainfall or little moisture.

SURFACE PREPARATION:

New Work:

1. Concrete and plaster surfaces must be primed with Masonry Primer.
2. Wooden surfaces must be primed with Wood Primer.
3. Metal surfaces must be primed with RP4, excluding very smooth surfaces e.g. New mild steel, galvanising or aluminium which must be coated with Vinyl Wash Primer/Acid Etch Primer.

Previously Painted Surfaces:

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Old enamel or oil paints must be sanded and suitably primed.
4. Chalky surfaces must be well brushed and sealed with Masonry Primer.

General:

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with a suitable Masonry Crack Filler, and primed with Masonry Primer, before application of the paint system.
3. Consult our sales staff for application onto any other substrate.

APPLICATION:

Ready to use. Brush, roller or airless spray application. Apply 2 coats.
Clean with water.

TECHNICAL DATA:

SG:	1.43 +/- 0.05
Viscosity:	100 - 105 KU
Drying Time: (T)	1 hour
@ 25°C: (H)	4 hours
Over coating:	2 hours
Solid Mass:	48 - 52%
Finish:	Matt
Scrubs:	< 1 000
Spread Rate:	6 - 8m ² / Lt
Colour Range:	White only