



# DEKABOND

**CODE:**

**DEB**

**DESCRIPTION:**

A multi-purpose flexible waterproofing system of exceptional quality and versatility. Used for parapet walls, flat roofs, gutters, flashings, etc. Can be used on new and previously painted surfaces.

**PRODUCT BENEFITS:**

Membrane built-in and ready for use. More advantages than bitumen type waterproof coatings. Easy application. Clean up with water.

**SURFACE PREPARATION:**

Surface to be painted must be thoroughly clean, dry and free from loose flaking paint, algae, dirt, grime and other foreign contaminants. Large cracks must be made good with approved adhesive filler. Corroded metal surfaces must be correctly prepared and primed with Dekade Rust Primer. Previously gloss enamel surfaces must be well sanded to remove the gloss and achieve a smooth matt surface. Wash all surfaces with sugar soap and water.

**GENERAL:**

Do not apply during cold and wet weather. Whilst Dekade Dekabond is designed to give extended life, it is still advisable to give a maintenance coat every 2 - 3 years. Full cure is only reached after 7 days. Do not use powder fillers or cement for filling.

**APPLICATION:**

Stir with flat paddle before use. Ready for use by brush or roller. Thinning - DO NOT THIN. Clean up with water.

**TECHNICAL DATA:**

Type:	Acrylic copolymer with selected fibres
Drying Time: (T)	4 Hours
@ 25°C (H):	24 Hours
Recoat:	24 Hours
SG:	1.25 - 1.27
Viscosity:	100 - 110 KU
Solids by Volume:	34 - 36%
Spread rate:	Approx. 1m <sup>2</sup> /Lt depending on substrate porosity.
Gloss Level:	Sheen
Solids by Mass:	55 - 58%
Flashpoint:	Non-flammable
Pack Sizes:	5lt & 20lt
Colour Range:	Grey and White
Appearance:	Light Texture

**Health and Safety:**

Refer to Material Safety Data Sheet