



ECOPRIME

CODE:

ECP

DESCRIPTION:

Eco-friendly primer for interior/exterior use. Specifically recommended as a primer for new dry plaster and other gypsum based products, brick, concrete, fibre cement and various types of composition boarding. Suitable as a primer/sealer for penetrating and binding powdery surfaces.

PRODUCT BENEFITS:

A low VOC, high hiding water based white plaster primer. Exhibits good alkali resistance with good sealing properties. Low odour. No obnoxious fumes. Acts as a primer and sealer. Quick drying. Easy clean up with water. Environmentally friendly.

SURFACE PREPARATION:

New Work:

Surfaces must be clean, dry and free from all foreign contaminants. New plaster moisture content not to exceed 15% before application.

SURFACE PREPARATION:

Previously painted surfaces:

Powdery, chalky surfaces must be thoroughly wire-brushed/sanded. All loose and flaking paint to be removed.

GENERAL:

Not to be used as a primer on metal. Optimum results achieved if moisture content does not exceed 15% on masonry surfaces. Do not paint during wet or cold weather.

APPLICATION:

Stir thoroughly with flat paddle before use. Ready for use by brush or roller or airless spray. Brush application preferred for chalky surfaces. Thin up to 15% with clean water for chalky surfaces. Clean up immediately with degreaser and clean water.

TECHNICAL DATA:

Type:	Acrylic Emulsion Primer
Drying Time: (T)	1 Hour
@ 25°C (H):	2 Hours
Recoat:	2 Hours
Viscosity:	95 - 100 KU
SG:	1.40 - 1.42
Solids by Volume:	40 - 42%
Spread rate:	Approx. 8m ² /Lt
Solids by Mass:	62 - 64%
Flashpoint:	Non flammable
Colour Range:	White
Pack Sizes:	5lt & 20lt
Finish:	Matt

Health and Safety:

Refer to Material Safety Data Sheet