



EGGSHELL ENAMEL

CODE:

EGE

Description:

Superior quality eggshell enamel for interior use. For the decoration and protection of all interior surfaces where a low sheen finish is required. Recommended for plaster, metal and wood that have been correctly primed & undercoated. Ideal for kitchens, bathrooms & children's rooms.

Product Benefits:

Excellent flow and levelling. Quick drying. Easy application. Uniform eggshell low sheen appearance.

SURFACE PREPARATION:

New Work:

WOOD: Apply 2 coats of Dekade Universal Undercoat. PLASTER: Surface must be clean and dry. Apply 1 coat Surface conditioner and Universal Undercoat. Allow 24 hours drying time between coats. METAL: Must be free from rust and oil. Prime with Zinc Phosphate Primer and Universal Undercoat. Allow 24 hours drying time between coats.

Previously Painted Surfaces:

Loose flaking paint and efflorescence must be completely removed. All bare wood and metal surfaces to be coated with appropriate primer & undercoat. Gloss and Oil surfaces must be sanded and wiped down with a damp cloth. Chalky surfaces must be thoroughly sanded before sealing with Surface Conditioner. Kitchen walls without exception to be washed down with sugar soap.

GENERAL:

Do not paint during cold and wet weather.
Do not apply to unprimed metal surfaces.

APPLICATION:

Stir thoroughly with flat paddle before use. Ready for use with brush or mohair roller. Thin with Mineral Turps for spray application. Clean up with Mineral Turps / Brush and Rinse Cleaner / Degreaser.

TECHNICAL DATA:

SG:	1.28 - 1.30
Viscosity:	68 - 72 KU
Drying Time: (T)	4 hours
@ 25°C (H):	24 hours
Recoat:	16 hours
Solid Mass:	66 - 72%
Finish:	Low Sheen
Volume Solids:	46 - 48%
Spread rate:	Approx. 10m ² /Lt depending on surface profile and porosity.
Pack Sizes:	500ml, 1L & 5L
Flash Point:	37°C
Recommended DFT:	20 - 30 microns
Colour Range:	White and tint bases

Health and Safety:

Refer to Material Safety Data Sheet