

PREMIUM INTERIOR ENAMEL PAINT

EGGSHELL ENAMEL

**CODE:****DES****Description:**

Superior quality Eggshell Enamel for interior use. Recommended for plaster, metal and woodwork after appropriate primers and undercoats have been applied.

Product Benefits:

Excellent flow and levelling. Uniform eggshell low sheen appearance. Quick drying. Easy application.

SURFACE PREPARATION:**New Work:**

1. Concrete and plaster surfaces must be primed with Alkali Resistant Primer.
2. Wooden surfaces must be primed with Wood Primer and Universal undercoat.
3. Metal surfaces must be primed with RP4, excluding very smooth surfaces e.g. New Mild steel, galvanising or aluminium which must be coated with Vinyl Wash Primer I Acid Etch Primer and Universal Undercoat.

Previously Painted Surfaces:

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Old enamel or oil paints must be sanded and suitably primed.
4. Chalky surfaces must be well brushed and sealed with Alkali Resistant Primer.

General:

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with a suitable Masonry Crack Filler, and primed with Masonry Primer, before application of the paint system.
3. Consult our sales staff for application onto any other substrate.
4. Not compatible with pliolite based products e.g. Masonry Primer.

APPLICATION:

Ready to use. Brush or mohair application.
Apply 2 coats sanding lightly between coats.
Clean with mineral Turpentine.

TECHNICAL DATA:

SG:	1.29 +/- 0.05
Viscosity:	68 - 72 KU
Drying Time: (T)	4 hours
@ 25°C: (H)	24 hours
Overcoating:	16 hours
Solid Mass:	66 - 72%
Gloss @ 60°:	20 - 30% Sheen
Spread Rate:	7 - 8m ² / Lt
Colour Range	White
Bases:	Pastel, Deep, Transparent

Note: Certain transparent colours may require a minimum of 3 coats to achieve total obliteration.