

PREMIUM WATERPROOFER WITH HIGH ELASTICITY

ELASTIPROOF™



CODE:

DEB

Description:

Elastiproof is a superior quality, seamless liquid applied, pure acrylic, waterproofing product with exceptional elasticity and longevity. Suitable coating to encapsulate asbestos surfaces.

Product Benefits:

Elastiproof is suitable for new and redecoration work and has excellent adhesion and exceptional resistance to UV light. Elastiproof can be used with or without a membrane depending on application, and withstands tremendous movement within the substrates.

SURFACE PREPARATION:

New Work:

1. Concrete and plaster surfaces must be primed with Masonry Primer.
2. Wooden surfaces must be primed with Wood Primer.
3. Metal surfaces must be primed with RP4, excluding very smooth surfaces e.g. New Mild steel, galvanising or aluminium which must be coated with Vinyl Wash Primer / Acid Etch Primer.

Previously Painted Surfaces:

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Old enamel or oil paints must be sanded and suitably primed.
4. Chalky surfaces must be well brushed and sealed with Masonry Primer.

General:

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with a suitable Masonry Crack Filler, and primed with Masonry Primer, before application of the paint system.
3. Consult our sales staff for application onto any other substrate.

APPLICATION:

Ready to use. Brush or roller or airless spray application.
Apply 2 coats. With use of membrane, apply a minimum of 3 coats.
Clean with water.

TECHNICAL DATA:

SG:

1.21 - 1.25

Viscosity:

138 – 140 KU

Drying Time: (T)

4 hours

@ 25°C: (H)

24 hours. 24 hours saturation overcoat.

Overcoating:

6 hours

Solid Mass:

+/- 50%

Finish:

Low Sheen

Spread Rate:

1Lt - 2Lt / m² (system)

4 m² / Lt per coat

Colour Range:

White, Red, Grey