



# GOLD LABEL SHEEN

**CODE:**

**GLS**

**DESCRIPTION:**

Gold Label Sheen is a luxurious, washable and durable interior/exterior, pure acrylic wall coating, which dries to a silky-smooth sheen finish, which gives excellent wear and dirt removal properties. Suitable for direct application to new and previously painted plaster, composition board, fibre cement, wood and metal surfaces that have been correctly prepared, primed and undercoated.

**PRODUCT BENEFITS:**

Quick drying. Low odour. Equipment easily cleaned in water. Non-Yellowing. Outstanding exterior durability.

**SURFACE PREPARATION:**

**New Work:**

**CONCRETE/CEMENT PLASTER:** Apply 1 coat Dekade Surface Conditioner and allow 24 hours to dry. **GYPSUM PLASTER/FIBRE CEMENT:** Apply 1 coat Surface Conditioner, thinned 10% with Mineral Turps and allow 24 hours to dry. **GALVANISED IRON:** Prime with 1 coat Dekade WB Galvanised Iron Primer and allow 4 hours to dry. **METAL SURFACES:** Loose surface rust must be totally removed. Prime with Dekade Zinc Phosphate Primer, followed by Dekade Universal Undercoat. Allow 24 hours between coats.

**Previously Painted Surfaces:**

Loose flaking paint and efflorescence must be completely removed. All bare exposed metal areas must be spot primed with the appropriate primer. Remove all surface rust and prime with 2 coats of Dekade Rust and Metal Primer. Gloss/Oil Surfaces to be thoroughly sanded and wiped down with a damp cloth. Apply 1 coat Universal Undercoat and allow 24 hours to dry. Chalky surfaces must be thoroughly sanded before applying 1 coat Surface Conditioner diluted 10% with Mineral Turpentine. Kitchen walls without exception to be washed down with sugar soap.

**PRECAUTIONS:**

Do not apply during cold, wet conditions.  
Do not apply directly to unprimed metal surfaces.

**APPLICATION:**

Stir thoroughly with flat paddle before use. Ready for use by brush, roller or airless spray. Thinning is not normally necessary, use clean water if required. Clean up with water.

**TECHNICAL DATA:**

Type:	Pure Acrylic
SG:	1.26 - 1.27
Drying Time: (T)	2 hours
@ 25°C (H):	8 hours
Recoat:	4 hours
Finish:	Sheen
Viscosity:	95 - 100 KU
Solids Volume:	30 - 35%
Solids Mass:	43 - 45%
Spread Rate:	Approx. 10 - 12m <sup>2</sup> /Lt depending on surface profile and porosity.
Flashpoint:	Non-flammable
Colour Range:	Black, White and tint bases
Pack Size:	1L, 5L & 20L

**Health and Safety:**

Refer to Material Safety Data Sheet