

PREMIUM TEXTURED INTERIOR/EXTERIOR PAINT

MARVATEX™



CODE:

DMX

Description:

A strong flexible pure acrylic texture coating with a low relief.

Product Benefits:

Formulated as a decorative textured finish. Its special properties ensures the coverage of hairline cracks with the flexibility to cope with the expansion and contraction of plaster surfaces.

SURFACE PREPARATION:

New Work:

1. Concrete and plaster surfaces must be primed with Masonry Primer.
2. Wooden surfaces must be primed with Wood Primer.
3. Metal surfaces must be primed with RP4, excluding very smooth surfaces e.g. new mild steel, galvanising or aluminium which must be coated with Vinyl Wash Primer/Acid Etch Primer.

Previously Painted Surfaces:

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Old enamel or oil paints must be sanded and suitably primed.
4. Chalky surfaces must be well brushed and sealed with Masonry Primer.

General:

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with a suitable Masonry Crack Filler, and primed with Masonry Primer, before application of the paint system.
3. Consult our sales staff for application onto any other substrate.

APPLICATION:

Ready to use with brush or roller application. Apply 2 coats.
Clean with water.

TECHNICAL DATA:

SG:	1.34 +/- 0.05
Viscosity:	130 - 135 KU
Drying Time: (T)	1 hour
@ 25°C: (H)	4 hours
Overcoating:	4 hours
Solid Mass:	50 - 55%
Finish:	Textured
Spread Rate:	4 - 5m ² /Lt depending on substrate
Scrubs:	>10 000
Colour Range:	White and Pastel shades