

PREMIUM ALKALI-RESISTANT PRIMER

# MASONRY PRIMER

**CODE:****DMP 01****Description:**

Pliolite based primer with excellent binding properties.

**Product Benefits:**

Dries to a matt finish providing a base for acrylic coatings.  
Combines excellent alkali resistance with excellent sealing properties.  
A sound primer for providing a key on all plaster surfaces.

**SURFACE PREPARATION:****New work**

1. Concrete and plaster surfaces must be left 4 - 6 weeks to dry.
2. Moisture content of plaster should be <15%.

**Previously Painted Surfaces:**

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Chalky surfaces must be well brushed before sealing with Masonry Primer.

**General:**

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with a suitable Masonry Crack Filler, and primed with Alkali Resistant Primer, before application of the paint system.
3. Consult with sales staff for application onto any other substrate.
4. Do not overcoat with alkyd based products e.g. Gloss Enamel.

**APPLICATION:**

Ready to use. Apply by brush or roller application. Apply 1 coat.  
Clean with mineral turpentine.

**TECHNICAL DATA:**

<b>SG:</b>	1.36 +/- 0.05
<b>Viscosity:</b>	80 - 85 KU
<b>Drying Time: (T)</b>	2 hours
<b>@ 25°C: (H)</b>	24 hours
<b>Overcoating:</b>	8 - 12 hours
<b>Solid Mass:</b>	62 - 68%
<b>Finish:</b>	Matt
<b>Spread Rate:</b>	7 - 8m <sup>2</sup> /Lt depending on substrate porosity
<b>Colour Range:</b>	White