

PREMIUM QUALITY PRIMER FOR RAW WOOD SURFACES

PINK WOOD PRIMER

**CODE:****DPU 03****Description:**

An oil based primer coat for interior and exterior raw wooden surfaces.

Product Benefits:

Provides nourishment and protection to timber and has excellent adhesion for subsequent overcoating with undercoat & gloss topcoat.

SURFACE PREPARATION:**New Work:**

1. Apply to wooden surfaces only. Knots to be treated with knot sealer.
2. Metal surfaces eg nailheads must be primed with RP4.

Previously Painted Surfaces:

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Do not apply over existing paint.

General:

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Special attention must be given to painting the end grain to avoid moisture penetration.
3. Wood primer must be overcoated with Universal Undercoat before applying the topcoat.
4. Do not apply onto plasterwork, metal or existing paint

APPLICATION:

Ready to use. Apply by brush for proper wetting and penetration of the primer into the wood. Apply one coat. Clean with Mineral Turpentine.

TECHNICAL DATA:

SG:	1.47 +/- 0.05
Viscosity:	65 - 70 KU
Drying Time: (T)	4 hours
@ 25°C: (H)	24 hours
Overcoating:	16 hours
Solid Mass:	66 - 68%
Finish:	Matt
Spread Rate:	7 - 8m ² / Lt depending on substrate porosity.
Colour Range:	Pink