

PREMIUM QUALITY VERSATILE PREP FOR PLASTER

PLASTER PRIMER

**CODE:****DUC 02****Description:**

A primer for new, dried plaster, brick, concrete, masonite, and other types of composition board substrates, where the preferred topcoat is an enamel.

Product Benefits:

Alkali Resistant primer with excellent sealing properties.

SURFACE PREPARATION:**New Work:**

1. Concrete and plaster surfaces must be cured before priming with Alkali Resistant Primer.

Previously Painted Surfaces:

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Chalky surfaces must be well brushed before sealing with alkali resistant primer.

General:

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with Masonry filler, and spot primed with Plaster Primer.
3. Consult our sales staff for application onto any other substrate.

APPLICATION:

Ready to use. Brush application to ensure penetration is preferred. Apply one coat. Clean with Mineral Turpentine.

TECHNICAL DATA:

SG:	1.52 +/- 0.05
Viscosity:	70 - 75 KU
Drying Time: (T)	2 hours
@ 25°C: (H)	24 hours
Overcoating:	16 hours
Solid Mass:	55 - 62%
Finish:	Matt
Spread Rate:	6 - 8m ² / Lt depending on substrate porosity
Colour Range:	White only