

PREMIUM WATERPROOFING PAINT

PLASTICLAD™



CODE:

DPC

Description:

Plasticlad is a superior quality vertical waterproofing emulsion with a sheen finish. It is an excellent decorative coating, having very low dirt retention. Plasticlad has excellent hiding power and is ideal for new work and redecoration.

Product Benefits:

High grade washable wall finish for interior / exterior use. Provides suitable waterproofing properties for most external elevations / vertical walls. Suitable for application onto most substrates provided they have been properly primed.

SURFACE PREPARATION:

New Work:

1. Concrete and plaster surfaces must be primed with Masonry Primer.
2. Wooden surfaces must be primed with Wood Primer.
3. Metal surfaces must be primed with RP4, excluding very smooth surfaces e.g. New Mild steel, galvanising or aluminium which must be coated with Vinyl Wash Primer / Acid Etch Primer.
4. Asbestos / Cement tiles should be treated with antifungal wash prior to application.

Previously Painted Surfaces:

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Old enamel or oil paints must be sanded and suitably primed.
4. Chalky surfaces must be well brushed and sealed with Masonry Primer.

General:

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with a suitable Masonry Crack Filler, and primed with Masonry Primer, before application of the paint system.
3. Consult our sales staff for application onto any other substrate.

APPLICATION:

Ready to use with brush, roller or airless spray application. Apply 2 coats. Clean with water.

TECHNICAL DATA:

| | |
|------------------|--|
| SG: | 1.32 +/- 0.05 |
| Viscosity: | +/- 115 KU |
| Drying Time: (T) | 2 hours |
| @ 25°C (H): | 4 hours |
| Over coating: | 4 hours |
| Solid Mass: | +/- 50% |
| Finish: | Low Sheen |
| Solvent: | Water |
| Spread rate: | 6 - 7m ² /Lt depending on substrate porosity. |
| Scrubs: | 10 000+ |
| Colour Range: | White, Pastel |
| Gloss @ 85°: | 10-15% |

Note: Certain transparent colours may require a minimum of 3 coats to achieve total obliteration.