

LUXURY INTERIOR/EXTERIOR PAINT

## PREMIER SHEEN™



**CODE:**

**DPS**

**Description:**

A high quality, sheen, pure acrylic. Excellent scrub resistance. Recommended for high traffic areas.

**Product Benefits:**

Washable and flexible with excellent water resistance. Excess of 15 000 scrubs for high traffic areas.

**SURFACE PREPARATION:**

**New Work:**

1. Concrete and plaster surfaces must be primed with Masonry Primer.
2. Wooden surfaces must be primed with Wood Primer.
3. Metal surfaces must be primed with RP4, excluding very smooth surfaces e.g. New Mild steel, galvanising or aluminium which must be coated with Vinyl Wash Primer / Acid Etch Primer.
4. Asbestos / Cement tiles should be treated with antifungal wash prior to application.

**Previously Painted Surfaces:**

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Old enamel or oil paints must be sanded and suitably primed.
4. Chalky surfaces must be well brushed and sealed with Masonry Primer.

**General:**

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with a suitable Masonry Crack Filler, and primed with Masonry Primer, before application of the paint system.
3. Consult our sales staff for application onto any other substrate.

**APPLICATION:**

Ready to use with brush, roller or airless spray application. Apply 2 coats. Clean with water.

**TECHNICAL DATA:**

SG:	1.35 +/- 0.05
Viscosity:	95 - 100 KU
Drying Time (T):	40 Minutes
@ 25°C (H):	4 hours
Over coating:	2 hours
Solid Mass:	45 - 50%
Finish:	Sheen
Spread Rate:	8 - 10m <sup>2</sup> /Lt - Depending on substrate porosity.
Scrubs:	> 15 000
Colour Range:	White (Bases - Pastel, Deep and Transparent)
Gloss @ 85°	15-18%

Note: Certain transparent colours may require a minimum of 3 coats to achieve total obliteration.