



RAFTER COAT

CODE:

RFP

DESCRIPTION:

Rafter Coat is a quality, high opacity Acrylic PVA suitable for interior/ exterior use. Ideally for rafters but can be used for direct application to new and previously painted plaster, concrete, brickwork, composition boards, fibre cement, wood and metal surfaces that have been correctly prepared and primed.

PRODUCT BENEFITS:

Easily applied by brush, roller and airless spray.
Quick drying; allows two coats to be applied in one day.
Low odour. Equipment easily cleaned in water.

SURFACE PREPARATION:

Loose flaking paint and efflorescence must be completely removed. All bare exposed metal areas must be spot primed with the appropriate primer and undercoat. Gloss/oil paint surfaces to be thoroughly sanded and wiped down with damp cloth. Chalky surfaces must be thoroughly sanded before applying Dekade Surface Conditioner.

PRECAUTIONS:

Do not apply during cold, wet conditions.
Do not apply directly to unprimed metal surfaces.

APPLICATION:

Stir thoroughly with flat paddle before use. Ready for use by brush or roller. Thinning is not normally necessary. Clean up with water.

TECHNICAL DATA:

Type:	Acrylic copolymer.
SG:	1.42 - 1.44
Drying Time: (T) @ 25°C (H):	1/2 - 1 hour 4 hours
Recoat:	4 hours
Finish:	Matt
Viscosity:	100 - 105 KU
Solids Volume:	33 - 36%
Solids Mass:	62 - 66%
Spread Rate:	Approx. 8m ² /Lt depending on surface profile and porosity.
Flashpoint:	Non-flammable
Colour Range:	Black & Brown
Pack Size:	5L & 20L

Health and Safety:

Refer to Material Safety Data Sheet