



STAINBLOK

CODE:

STB

DESCRIPTION:

Dekade Stainblok is specially formulated for painting over most unsightly stains, eg water marks etc.

PRODUCT BENEFITS:

Outstanding adhesion - will adhere to new and old alkyd enamels, concrete/plaster, brick and difficult chalky surfaces. No problem with drying. Will even dry at 0°C and 40°C. Excellent recoating - can be recoated after 4 hours drying time and at any time during its life. Outstanding durability. Resists moisture, alkali, industrial fumes, UV light and microbiological attack. Easy application by brush, roller or spray.

SURFACE PREPARATION:

Surface to be painted must be thoroughly clean, dry and free from all foreign contaminants and friable materials.
CHALKY PVA or LIMEWASH/DISTEMPER: Sand down all loose powder. Flaking paint must be completely removed. Apply 2 or more coats, undiluted depending on the severity of the stain.
ENAMEL SURFACES: Very lightly rub with 320 grit dry paper to a matt finish and wipe down with a damp cloth. Apply 2 or more coats, undiluted depending on the severity of the stain.

GENERAL:

Not to be used as a primer on metal.
Not recommended for painting over smoke stains.

APPLICATION:

Stir with flat paddle before use. Ready for use by brush or roller. Two coats is normally required and three in more severe cases. Allow a minimum of 4 hours drying time between coats. Thin and clean with Mineral Turpentine.

TECHNICAL DATA:

Type:	Modified Acrylic
Drying Time: (T)	1 Hour
Hard Dry:	4 Hours
Recoat:	7 Hours
SG:	1.28 - 1.30
Viscosity:	75 - 80 KU
Solids by Volume:	35 - 38%
Spread rate:	Approx. 8m ² /Lt depending on surface profile and porosity.
Gloss Level:	Matt
Solids by Mass:	58 - 62%
Flashpoint:	37°C
Pack Sizes:	500ml
Colour Range:	White
Resistant Properties:	Chemical Fumes - Excellent Microbial Attack - Excellent

Health and Safety:

Refer to Material Safety Data Sheet