



STOEP PAINT

CODE:

STP

DESCRIPTION:

An economical high gloss finish for direct application to new interior / exterior clean, dry wood floated cement, concrete floors & window sills. Can be applied to previously painted clean, dry and wax free surfaces.

PRODUCT BENEFITS:

Hard wearing and easy to clean. Easy to repaint when necessary. Prevents disintegration of cement floors.

SURFACE PREPARATION:

New Work:

NEW: Surfaces must be clean, dry and sound. Allow to dry for a minimum of 6 weeks before painting. Acid etch smooth surfaces to provide a "key"
OLD UNPAINTED: Scrub surfaces using Dekade Trade Degreaser to remove dirt, oils, fats, grease etc. Rinse with plenty of water and allow to dry. Acid etch smooth surfaces.

Previously Painted Surfaces:

Surfaces must be clean, dry and in sound condition before painting. All loose flaking paint must be removed. Rub entire surface with an abrasive paper to provide a "key". Remove wax using Dekade Trade Degreaser, wash down with water and allow to dry.

GENERAL:

Allow at least 24 hours after final coat before walking on floor. Do not apply to wet or damp surfaces. Not recommended for garage floors where spillage of oils & solvents may occur.

APPLICATION:

Stir with flat paddle before use. Ready for use by brush or roller. Thinning - Not necessary except for spray application. Clean up with Mineral Turpentine or Dekade Trade Degreaser.

TECHNICAL DATA:

Type:	Alkyd based
Drying Time: (T) @ 25°C (H):	4 Hours 24 Hours
Recoat:	16 Hours (overnight)
SG:	1.00 - 1.02
Viscosity:	60 - 65 KU
Solids by Volume:	33 - 35%
Spread rate:	Approx. 8m ² /Lt depending on substrate porosity.
Gloss Level:	Gloss
Solids by Mass:	43 - 46%
Flashpoint:	37°C
Pack Sizes:	500ml, 1lt, 5lt
Colour Range:	Black, Grey, Green and Red Oxide
Recommended DFT:	20 - 30 microns

Health and Safety:

Refer to Material Safety Data Sheet