



TRADE RANGE

TECHNICAL
DATA SHEET

NACTM
NATAL
ASSOCIATED
CHEMICALS

COURT DRESSING

CODE:

TCD

DESCRIPTION:

Dekade Trade Court Dressing is an excellent wearing dressing for use on tennis courts and other similar playing surfaces. Also suitable as an interior/exterior coating for plaster, concrete and fibre cement where a Chrome Oxide Green is required.

PRODUCT BENEFITS:

Specially formulated for sports clubs and tennis court owners.
Hard wearing dressing for new or old concrete courts.
Suitable for well weathered tarmac courts.
Excellent water and alkali resistance. Non-skid, Matt finish.

SURFACE PREPARATION:

New Work:

All surfaces must be clean, dry and free from all foreign contaminants.
Apply first coat Trade Court Dressing thinned 10% with water.
Allow to dry. Apply second coat Dressing undiluted.

Previously Painted Surfaces:

Loose flaking paint must be completely removed (ideally by water blasting).
Ensure surface is free of fungi, algae, dirt, dust, oil and other surface contaminants. Patch prime bare areas with Trade Court Dressing diluted 10% with water and allow to dry. Apply second coat Dressing undiluted.

GENERAL:

Do not paint during cold and wet weather. Do not apply to unprimed metal surfaces. Do not use on soft bituminous (slurry seal type) courts.
Allow a minimum of 3 days cure before court is put to use.

APPLICATION:

Stir thoroughly with flat paddle before use.
Thinning ratio: see above. Clean up with water.

TECHNICAL DATA:

| | |
|-------------------|--------------------------------|
| Type: | Acrylic Copolymer |
| Drying Time: (T) | 1/2 - 1 Hour |
| @ 25°C (H): | 4 Hours |
| Recoat: | 4 Hours |
| Viscosity: | 80 - 90 KU |
| SG: | 1.28 - 1.32 |
| Solids by Volume: | 35 - 37% |
| Spread rate: | Approx. 6 - 8m ² /L |
| Solids by Mass: | 52 - 56% |
| Flashpoint: | Non-flammable |
| Colour Range: | Chrome Oxide Green |
| Pack Sizes: | 5lt & 20lt |
| Finish: | Matt |

Health and Safety:

Refer to Material Safety Data Sheet