



TRADE RANGE

TECHNICAL
DATA SHEET

NACTM
NATAL
ASSOCIATED
CHEMICALS

HIGH COVER

CODE:	THC
DESCRIPTION:	High Cover is a high opacity, economy PVA especially formulated for household application. Suitable for application to new dry concrete, brickwork and composition boarding where a matt, high opacity economy PVA is required.
PRODUCT BENEFITS:	Easily applied by brush or roller. Quick drying. Dries to a matt finish - masks imperfections.
SURFACE PREPARATION:	Surface to be painted must be thoroughly clean, dry and free from all foreign contaminants. Loose, flaking paint and efflorescence must be completely removed from previously painted surfaces. Old enamel surfaces to be thoroughly sanded and wiped down with damp cloth. Chalky surfaces must be thoroughly sanded before applying 1 coat Plaster Primer diluted 10% with Mineral Turpentine.
GENERAL:	Do not apply in cold and wet weather conditions. Do not apply to unprimed metal surfaces. Not recommended for areas where high scrub resistance and maximum durability is required.
APPLICATION:	Stir thoroughly with flat paddle before use. Ready for use by brush, roller or airless spray. Thinning not normally necessary. Clean up with water.
TECHNICAL DATA:	
Type:	Acrylic Copolymer.
SG:	1.44 - 1.46
Drying Time: (T) @ 25°C (H):	1 hour 4 hours
Recoat:	2 hours
Finish:	Matt
Viscosity:	100 - 105 KU
Solids Volume:	29 - 32%
Solids Mass:	48 - 52%
Spread Rate:	Approx. 8m ² /Lt depending on surface profile and porosity.
Flashpoint:	Non-flammable
Colour Range:	White
Pack Size:	5L & 20L
Health and Safety:	Refer to Material Safety Data Sheet