



TRADE RANGE

TECHNICAL
DATA SHEET

NACTM
NATAL
ASSOCIATED
CHEMICALS

ROAD PAINT

CODE:

TRP

DESCRIPTION:

Dekade Trade Road Paint is used for direct application to new or previously painted bitumen or concrete road surfaces. May be used for sign writing on roads and parking lots. Useful sealer for certain types of bleeding surfaces.

PRODUCT BENEFITS:

Quick drying road marking paint with excellent road surface durability. For use on bitumen and concrete surfaces. Good visibility day and night. Can be applied by brush roller or spray.

SURFACE PREPARATION:

All surfaces must be clean, dry and free from any loose grit or gravel.

GENERAL:

As this material dries quickly do not attempt to work the brush or roller too much over the same area. Apply by layering an even coat. Not recommended for showroom floors due to matt finish. It soils easily. Not recommended as a decorative finish or as a cure for damp problems.

APPLICATION:

Stir thoroughly with flat paddle before use. Ready for use by brush or roller. Thin with Trade Road Paint Thinner for spray application and for brush application where necessary. Clean up - Trade Road Paint Thinner or Xylene.

TECHNICAL DATA:

Type:	Alkyd based
Drying Time: (T)	10 - 15 minutes
@ 25°C (H):	30 - 40 minutes
Recoat:	N/A Apply only one coat
Viscosity:	75 - 85 KU
SG:	1.40 - 1.42
Solids by Volume:	33 - 36%
Spread rate:	2 - 4m ² /L (new work) 4 - 6m ² /L (repaint)
Solids by Mass:	42 - 46%
Flashpoint:	<10°C
Colour Range:	Black, White, Red and Golden Yellow
Pack Sizes:	500ml, 1lt, 5lt & 20lt
Finish:	Matt
Recommended DFT:	70 microns (new work) 30 microns (repaint)

Health and Safety:

Refer to Material Safety Data Sheet