



TRADE RANGE

TECHNICAL
DATA SHEET

NACTM
NATAL
ASSOCIATED
CHEMICALS

RUBBERCOAT

CODE:

TRC

DESCRIPTION:

Rubbercoat is a multi-purpose flexible waterproofing system of exceptional quality and versatility. Used as a general purpose waterproofing system for parapet walls, flat roofs, gutters, flashings etc. Can be used on new and previously painted surfaces.

PRODUCT BENEFITS:

Built-in reinforcement and ready for use. More advantageous than bitumen type waterproof coatings. Easy application. Clean up with water.

SURFACE PREPARATION:

Surface to be painted must be thoroughly clean, dry and free from loose flaking paint, algae, dirt, grime or any other foreign contaminants. Large cracks and holes must be made good with approved adhesive filler. Corroded metal surfaces must be correctly prepared and primed with Dekade Rust and Metal Primer. Gloss enamel surfaces must be well sanded to remove the gloss and achieve a smooth matt surface. Wash all surfaces with sugar soap and water.

GENERAL:

Do not use during cold and wet weather. Whilst Rubbercoat is designed to give extended life, it is still advisable to give a maintenance coat every 2 - 3 years. Full cure is only reached after 7 days. Do not use powder fillers or cement for filling.

APPLICATION:

Stir thoroughly with flat paddle before use. Ready for use by brush or roller. Thinning - DO NOT THIN. Clean up with water.

TECHNICAL DATA:

Type:	Acrylic copolymer with selected reinforcement
Drying Time: (T)	2 Hours
@ 25°C (H):	24 Hours
Recoat:	4 Hours
Full Cure:	7 Days
Viscosity:	110 - 120 KU
SG:	1.09 - 1.12
Solids by Volume:	37 - 40%
Spread rate:	Approx. 1m ² /L depending on surface profile and porosity.
Solids by Mass:	60 - 62%
Flashpoint:	Non-flammable
Colour Range:	Grey and Black
Pack Sizes:	5lt & 20lt
Finish:	Sheen
Appearance:	Heavy Texture

Health and Safety:

Refer to Material Safety Data Sheet