



TRADE RANGE

TECHNICAL
DATA SHEET

NACTM
NATAL
ASSOCIATED
CHEMICALS

SUPER MATT

CODE:

TSM

DESCRIPTION:

Super Matt is a quality washable interior/exterior matt emulsion. Suitable for direct application to new and previously painted plaster, composition board, fibre cement, wood and metal surfaces that have been correctly prepared and primed.

PRODUCT BENEFITS:

Easily applied by brush, roller or airless spray. Quick drying. Low odour. Non-yellowing white. Easy clean up with water.

SURFACE PREPARATION:

Surface to be painted must be thoroughly clean, dry and free from all foreign contaminants. Loose, flaking paint and efflorescence must be completely removed from previously painted surfaces. All bare exposed metal areas must be spot primed with the appropriate primer and undercoat. Gloss and oil paint surfaces to be thoroughly sanded and wiped down with damp cloth. Chalky surfaces must be thoroughly sanded before applying 1 coat Plaster Primer. Kitchen walls without exception to be washed down with sugar soap.

GENERAL:

Do not apply in cold and wet weather conditions.
Do not apply to unprimed metal surfaces.

APPLICATION:

Stir thoroughly with flat paddle before use. Ready for use by brush, roller or airless spray. Clean up with water.

TECHNICAL DATA:

Type:	Acrylic Copolymer.
SG:	1.44 - 1.46
Drying Time: (T) @ 25°C (H):	1 hour 4 hours
Recoat:	2 hours
Finish:	Matt
Viscosity:	85 - 95 KU
Solids Volume:	30 - 36%
Solids Mass:	50 - 55%
Spread Rate:	Approx. 8m ² /Lt depending on surface profile and porosity.
Flashpoint:	Non-flammable
Colour Range:	White and tint bases
Pack Size:	5L & 20L

Health and Safety:

Refer to Material Safety Data Sheet