



TRADE RANGE

TECHNICAL  
DATA SHEET

**NAC**<sup>TM</sup>  
NATAL  
ASSOCIATED  
CHEMICALS

# UNDERCOAT

**CODE:**

**TUC**

**DESCRIPTION:**

Dekade Trade Undercoat is an intermediate coating for all decorative paints. Steel and plaster etc. must have the correct primer before applying a coat of Trade Undercoat.

**PRODUCT BENEFITS:**

Good quality general purpose undercoat for use under decorative topcoats. Excellent adhesion on correctly prepared primed steel, wood and plaster surfaces. Provides a smooth base with good binding properties. Easily applied by brush or roller.

**SURFACE PREPARATION:**

All surfaces must be clean, dry and correctly primed with an appropriate primer. A hard dry film should be lightly sanded. Loose and flaking paint must be completely removed and bare exposed areas correctly primed with the appropriate primer.

**GENERAL:**

Do not paint during cold and wet weather.  
Do not apply to bare metal, cement plaster and fibre cement.

**APPLICATION:**

Stir thoroughly with flat paddle before use. Ready for use by brush or roller. Thin if required with Mineral Turps. Clean up with Mineral Turps.

**TECHNICAL DATA:**

Type:	Alkyd Based
Drying Time: (T)	4 Hour
@ 25°C (H):	18 Hours
Recoat:	18 Hours
Viscosity:	68 - 72 KU
SG:	1.45 - 1.47
Solids by Volume:	38 - 40%
Spread rate:	Approx. 8m <sup>2</sup> /L at DFT 60 microns
Solids by Mass:	58 - 62%
Flashpoint:	37°C
Colour Range:	White
Pack Sizes:	5lt & 20lt
Finish:	Matt

**Health and Safety:**

Refer to Material Safety Data Sheet