

PREMIUM QUALITY UNIVERSAL UNDERCOAT

UNIVERSAL UNDERCOAT

**CODE:****DUC 01****Description:**

A high quality alkyd undercoat with excellent coverage and obliteration.

Product Benefits:

Excellent adhesion properties onto existing gloss enamels.
Designed to be overcoated with alkyd and emulsion topcoats.
Acts as an adhesion promoting barrier coat.

SURFACE PREPARATION:**New Work:**

1. Concrete and plaster surfaces must be primed with Alkyd Resisting Primer.
2. Wooden surfaces must be primed with Wood Primer.
3. Metal surfaces must be primed with RP4, excluding very smooth surfaces e.g. New Mild steel, galvanising or aluminium which must be coated with Vinyl Wash Primer/Acid Etch Primer.

Previously Painted Surfaces:

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Old enamel or oil paints must be sanded and suitably primed.
4. Chalky surfaces must be well brushed and sealed with Alkyd Resistant Primer.

General:

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with a suitable Masonry Crack Filler, and primed with Masonry Primer, before application of the paint system.
3. Consult our sales staff for application onto any other substrate.
4. Do not apply over pliolite based masonry products.
5. Do not overcoat with topcoats containing aggressive solvents e.g. Xylene.

APPLICATION:

Ready to use with brush, roller or airless spray application.
Apply 1 single coat. Clean with mineral turpentine.

TECHNICAL DATA:**SG:**

1.46 +/- 0.05

Viscosity:

68 - 72 KU

Drying Time: (T)

4 hours

@ 25°C: (H)

18 hours

Overcoating:

18 hours

Solid Mass:

55 - 62%

Finish:

Matt

Spread Rate:7 - 8m²/Lt depending on substrate**Colour Range:**

White only