

# MASTERDEC SOFT SHEEN

**CODE:****DMS****Description:**

A superior quality washable interior/exterior sheen emulsion paint. This product is suitable for application to new primed cement plaster, concrete, porous brickwork, suitably primed wood, metals, fibre cement, gypsum plaster and various types of building boards.

**Product Benefits:**

- This product offers excellent durability with a sheen finish.
- High whiteness and hiding properties.
- Very good scrubability and spreadability.
- Suitable for application by brush or roller.
- Easy clean up with water.

**SURFACE PREPARATION:**

Ensure all surfaces are clean, dry and free from dirt, oil, grease and any contaminants. Allow 16 hours drying time to all primed surfaces before applying topcoat.

**NEW WORK:**

1. Cement plaster, concrete, gypsum plaster, gypsum board, fibre cement and unglazed brick: Prime entire surface with Deco Plaster Primer.
2. Wood: Sand until smooth in the direction of the grain and dust off. Prime with Deco Wood Primer.
3. Mild Steel: Degrease with Deco Water-based Degreaser and rinse thoroughly with water until a water break-free surface is achieved. Remove any rust by wire brushing. Prime with Deco RP4.
4. Galvanised Steel: Clean with Deco Galvanised Iron Cleaner and rinse thoroughly with water until a water break-free surface is achieved. Prime with Deco Galvanised Iron Primer.

**PREVIOUSLY PAINTED SURFACES:**

1. Previously painted surfaces in a good condition: Remove loose and flaking paint by scraping and sanding. Clean with sugar soap powder solution to remove all surface contamination and chalky material. Rinse well with water until all traces of sugar soap is removed. Spot prime bare areas with a suitable primer. Sand glossy enamel surfaces to a matt finish and apply one coat of Deco Universal Undercoat.
2. Previously painted surfaces in a poor condition: Remove paint by scraping, sanding, etc and proceed as for New Work.

**FILLING:**

1. Cracks: fill defects with a suitable crack filler
2. Wood and Fibre-cement: Fill with an appropriate filler.

**Precautions:**

- Not recommended for areas where chemical resistance is required.
- To ensure colour consistency for a project ensure that batch numbers correspond.
- Conduct a small test over paintable flexible sealants to ensure compatibility as cracking may occur.

# MASTERDEC SOFT SHEEN - CONTINUED

**APPLICATION:**

- Application by brush, roller or airless spray.
- Apply two or more coats to ensure complete obliteration.
- Thinning not normally necessary.
- Clean up with clean water.

**TECHNICAL DATA:**

Type:	Modified Acrylic Emulsion
SG:	1.19 - 1.21
Drying Time: (T)	1 hour
Drying Time: (H)	4 hours
Solid Mass:	32 - 36%
Solids Volume:	22 - 26%
Finish:	Sheen
Viscosity:	95 - 100 KU
Spread Rate:	Approx 8m <sup>2</sup> /lt depending on surface profile and porosity.
Flash Point:	Non-flammable
Mixing:	Stir thoroughly with a flat paddle until homogenous and periodically during use.
Colours:	White, Pastel Base, Deep Base and Transparent Base.
Pack Size:	5L and 20L
Clean Up:	Water
Thinning:	Not recommended
Application Environment:	Surface Temperature: Min 10°C / Max 35°C Ambient Temperature: Min 10°C / Max 35°C Relative Humidity: Min 10% / Max 85%

Health and Safety: Refer to SDS.