

OPAL PVA

CODE:**OPA****DESCRIPTION:**

Opal PVA is a low cost PVA especially formulated for household application. Suitable for application to new dry concrete, brickwork and composition boarding where a low cost PVA is required.

PRODUCT BENEFITS:

Easily applied by brush or roller. Quick drying. Heavy bodied for good roller application. Dries to a matt finish - masks imperfections.

SURFACE PREPARATION:

Surface to be painted must be thoroughly clean, dry and free from all foreign contaminants.

GENERAL:

Do not apply in cold and wet weather conditions.
Do not apply to unprimed metal surfaces. Not recommended for areas where high scrub resistance and maximum durability is required.

APPLICATION:

Stir thoroughly with flat paddle before use. Ready for use by brush, roller or airless spray. Thinning not normally necessary, use clean water if required. Thinning will reduce opacity. Clean up with water.

TECHNICAL DATA:

Type:	Acrylic Copolymer.
SG:	1.40 +/- 0.05
Drying Time: (T)	1 hour
@ 25°C (H):	4 hours
Recoat:	2 hours
Finish:	Matt
Viscosity:	100 - 105 KU
Solids Volume:	16 - 18%
Solids Mass:	44 - 46%
Spread Rate:	Approx. 6m ² /Lt depending on surface profile and porosity.
Flashpoint:	Non-flammable
Colour Range:	White and range of ready mixed colours
Pack Size:	5L & 20L

Health and Safety:

Refer to Material Safety Data Sheet