

LUXURY INTERIOR/EXTERIOR PAINT

ULTRA SILK



CODE:

DVS

Description:

A top quality, highly washable pure acrylic with a smooth silk finish.

Product Benefits:

Dries to a hard yet flexible silk finish that will withstand repeated washing. Designed to be used as an internal decorative finish for high traffic areas. Excellent stain removal properties.

SURFACE PREPARATION:

New Work:

1. Concrete and plaster surfaces must be primed with Masonry Primer.
2. Wooden surfaces must be primed with Wood Primer.
3. Metal surfaces must be primed with RP4, excluding very smooth surfaces e.g. New Mild steel, galvanising or aluminium which must be coated with Vinyl Wash Primer/Acid Etch Primer.
4. Asbestos/Cement tiles should be treated with antifungal was prior to application.

Previously Painted Surfaces:

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Old enamel or oil paints must be sanded and suitably primed.
4. Chalky surfaces must be well brushed and sealed with Masonry Primer.

General:

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with a suitable Masonry Crack Filler, and primed with Masonry Primer, before application of the paint system.
3. Consult our sales staff for application onto any other substrate.

APPLICATION:

Ready to use with brush, roller or airless spray application. Apply 2 coats. Clean with water.

TECHNICAL DATA:

SG:	1.22 +/- 0.05
Viscosity:	100 - 105 KU
Drying Time: (T)	40 mins
@ 25°C: (H)	24 hours
Overcoating:	2 hours
Solid Mass:	40 - 45%
Gloss @ 85°:	25 - 30% Silk
Spread Rate:	7 - 9m ² /Lt dependent on substrate porosity
Scrubs:	> 15 000
Colour Range:	White
Bases:	Pastel, Deep, Transparent

NB: Certain transparent colours may require a minimum of 3 coats to achieve total obliteration.