

WALLS & CEILINGS

CODE:

BDW

Description:

A quality, heavy bodied matt acrylic emulsion.

Product Benefits:Easily applied by brush or roller. Quick drying.
Dries to a matt finish - masks imperfections.**SURFACE PREPARATION:****New Work:**

1. Concrete and plaster surfaces must be primed with Masonry Primer.
2. Wooden surfaces must be primed with Wood Primer.
3. Metal surfaces must be primed with RP4, excluding smooth surfaces e.g. New Mild Steel, Galvanising or Aluminium which must be coated with Vinyl Wash Primer/ Acid Etch Primer.

Previously Painted Surfaces:

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Old enamel or oil paints must be sanded and suitably primed.
4. Chalky surfaces must be well brushed and sealed with Masonry Primer.

General:

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with a suitable Masonry Crack Filler, and primed with Masonry Primer, before application of the paint system.
3. Consult our sales staff for application onto any other substrate.

APPLICATION:Ready to use with brush, roller or airless spray application. Apply 2 coats.
Clean with water.**TECHNICAL DATA:**

Type:	Acrylic Copolymer.
SG:	1.44 - 1.46
Drying Time: (T)	1 hour
@ 25°C (H):	4 hours
Recoat:	2 hours
Finish:	Matt
Viscosity:	100 - 105 KU
Solids Volume:	29 - 32%
Solids Mass:	48 - 52%
Spread Rate:	Approx. 8m ² /Lt depending on surface profile and porosity.
Flashpoint:	Non-flammable
Colour Range:	White
Pack Size:	5L & 20L

Health and Safety:

Refer to Material Safety Data Sheet